must include on FCC Form 405, the number of constructed VSAT units in its network.

[56 FR 66001, Dec. 20, 1991, as amended at 62 FR 5929, Feb. 10, 1997; 66 FR 31560, June 12, 2001]

§ 25.135 Licensing provisions for earth station networks in the non-voice, non-geostationary mobile-satellite service.

- (a) Each applicant for a blanket earth station license in the non-voice, non-geostationary mobile-satellite service shall demonstrate that transceiver operations will not cause unacceptable interference to other authorized users of the spectrum, based on existing system information publicly available at the Commission at the time of filing, and will comply with operational conditions placed upon the systems with which they are to operate in accordance with §25.142(b). This demonstration shall include a showing as to all the technical parameters, including duty cycle and power limits, under which the individual transceivers will operate.
- (b) Transceiver units associated with the non-voice, non-geostationary mobile-satellite service may not be operated on civil aircraft. All portable or hand-held transceiver units (including transceiver units installed in other devices that are themselves portable or hand-held) having a receiver operating in the 137-138 MHz band shall bear the following statement in a conspicuous location on the device: "This device may not be operated while on board a civil aircraft. It must be turned off at all times while on board such an aircraft." This subsection shall not apply to transceiver units whose receivers are incapable of radiating in the 108-137 MHz frequency bands.
- (c) Transceiver units in this service are authorized to communicate with and through U.S. authorized space stations only. No person shall transmit to a space station unless the specific transmission is first authorized by the space station licensee or by a service vendor authorized by that licensee.
- (d) Any transceiver unit associated with this service will be deemed, when communicating with a particular non-voice, non-geostationary mobile-sat-

ellite service system pursuant to paragraph (c) of this section, to be temporarily associated with and licensed to the system operator or service vendor holding the blanket earth station license awarded pursuant to §25.115(d). The domestic earth station licensee shall, for such temporary period, assume the same licensee responsibility for such transceiver as if such transceiver were regularly licensed to it.

[58 FR 68059, Dec. 23, 1993]

§ 25.136 Licensing provisions for the L-Band mobile-satellite service.

In addition to the technical requirements specified in §25.213, earth stations operating in the 1.6/2.4 GHz and 1.5/1.6 GHz Mobile Satellite Services are subject to the following operating conditions:

- (a) User transceiver units associated with the 1.6/2.4 GHz Mobile-Satellite Service or 2 GHz Mobile-Satellite Service may not be operated on civil aircraft unless the earth station has a direct physical connection to the aircraft cabin or cockpit communication system.
- (b) No person shall transmit to a space station unless the user transceiver is first authorized by the space station operator or by a service vendor authorized by that operator, and the specific transmission is conducted in accordance with the operating protocol specified by the system operator.
- (c) Any user transceiver unit associated with this service will be deemed, when communicating with a particular 1.6/2.4 GHz Mobile-Satellite Service or 2 GHz Mobile-Satellite Service system pursuant to paragraph (b) of this section, to be temporarily associated with and licensed to the system operator or service vendor holding the blanket earth station license awarded pursuant to §25.115(d). The domestic earth station licensee shall, for this temporary period, assume the same licensee responsibility for the user transceiver as if the user transceiver were regularly licensed to it.
- (d) Any mobile earth station (MES) associated with the Mobile Satellite Service operating in the $1530-1544~\mathrm{MHz}$ and $1626.5-1645.5~\mathrm{MHz}$ bands shall have